

# Samoiedo

## ICE-CREAM FAN ASSISTED COOLING

SGL 1300 G/G/G 2T



TENSION  
230V - 50HZ



LED LIGHTING  
2x1200 lm



### Technical Information

| LAYOUT |                           |                           | SHELVES L X P (MM) - NR | VOLUME  | GROSS  | NET    | COMPRESSOR          |
|--------|---------------------------|---------------------------|-------------------------|---------|--------|--------|---------------------|
|        | L 2050<br>P 620<br>H 1860 | L 2080<br>P 650<br>H 2030 | 565x445 -15             | Lt 1388 | Kg 511 | Kg 478 | Watt<br>750+750+750 |

### Optionals

- Key closing
- Wire shelf n.1
- Glass shelf n.1
- Shelf for glass and grids (n.4)
- Suction cup (n.4)
- Kit of glass shelves for static system
- Kit adjustable feet
- Looking-glass (n. 1) (except for 520 model)
- Glass with altitude valves (for installations above 800 m)
- "No-fog" door or rear glass for negative display case (except for 250 model)
- Power supply 220 V 60 HZ - power supply 115 V 60 HZ
- Water condensing system for each refrigerating group
- System developed for negative, static display cases (n.1) (except for 250, 350, 520 and 700 models)
- Remote motor unit (n. 1) (up to 10 mt.)
- Hot gas defrosting for each refrigerating group (Only single units)
- 3rd led for static negative display cases (1200 Lumen) (except for 520 models)
- Wooden crate packing